

### General Product Information

Product Series: Reassurance (Stationary)

Output: 6000 Watts / 6.0 kW

Battery Capacity: 14.4 kWh


### Product Overview

Our MHW60120V UPS system delivers 6000 watts of Split-phase power with a 14.4 KWH battery bank, ready to activate instantly during an outage.

This free standing hardwire system wheels into place and with a single branch output it easily integrates into your building's electrical system. Its compact design makes it suitable for places where space is limited while its bigger capacity ensures uninterrupted power with large power and time requirements.



### Wiring Diagram



## AC Electrical Specifications

General AC		Input Line Power		Output Load Power	
Wattage	6000	Voltage	208	Voltage	208
Phase Type	Split	Conductor Size	10 AWG	Conductor Size	12 AWG
Surge Wattage	12000	Amperage	30	Amperage	20
Frequency	60	Wire Configuration	Hot, Hot, Neutral, Ground	Wire Configuration	Hot, Hot, Neutral, Ground
Waveform	Pure	Connection Spec	Terminal Block	Outlets/Breakers	1
Transfer Time	20 ms			Connection Type	2 Pole Breaker
Bypass Switch	Not Included				

## DC Electrical Specifications

Battery Type	AGM Lead Acid	Power Outage Alert	Optional
Battery Capacity	14.4 kWh	Remote Battery Monitor	Yes
DC Voltage	24	Alarm Dry Contacts	Yes

## Available Accessories

## Standards

Inverter	UL 1741
Battery	UL 94V-0

## Enclosure/System Specifications

Cabinet Material	Stainless Steel	Tower Count	1	Height (in)	53
Inverter Cabinet Count	2	Weight	1092 lb	Width (in)	28
Battery Module Count	3	Heat Output	1227 BTU	Depth (in)	16

## Dimensional Drawing

